

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
14 February 2002 (14.02.2002)


PCT

(10) International Publication Number
WO 02/13188 A1


- (51) International Patent Classification⁷: G11B 5/17, 11/105, 5/60
- (21) International Application Number: PCT/EP01/08580
- (22) International Filing Date: 25 July 2001 (25.07.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 00202818.1 9 August 2000 (09.08.2000) EP
- (71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors: PENNING, Frank, C.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). DEKKER, Ronald; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). MAAS, Henricus, G., R.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (74) Agent: SCHRIJNEMAEEKERS, Hubert, J., M.; Internationaal Octrooibureau B.V., Prof Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (national): CN, JP, KR.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

[Continued on next page]

(54) Title: METHOD OF MANUFACTURING A MAGNETIC HEAD HAVING A PLANAR COIL



(57) Abstract: A simple method of manufacturing a magnetic head having a head face and including a planar magnetic coil (7) which extends parallel to the head face. According to the method, the magnetic coil is formed at a first side of a first substrate (1). Thereafter, the first substrate provided with the magnetic coil is adhered with its first side to a side of a second substrate (9), whereafter material of the first substrate is removed from a second side of the first substrate, the second side being turned away from the first side, in order to form the head face, in such a manner that the magnetic coil is situated near to the head face.



WO 02/13188 A1

WO 02/13188 A1

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 02/13188

PCT/EP01/08580

Method of manufacturing a magnetic head having a planar coil

The invention relates to a method of manufacturing a magnetic head having a head face and including a magnetic coil which extends parallel to the head face.

5 Such a method is known from the paper IEEE Transactions on Magnetics, Vol. 25, No. 5, September 1989, pages 3190-3193. This paper describes a fabrication process for realizing thin film heads on silicon, called IC heads, for high-density magnetic recording. The fabrication process starts from a silicon wafer in which grooves are etched. In these grooves magnetic heads including conductor spirals are formed. At the end of the process air
10 bearing surfaces are formed and sliders are defined by etching before the wafer is diced into separate components.

 One way to realize high-density recording is to apply magneto-optical (MO) recording. In such a recording process data is written in a magnetic recording layer of a magnetic medium, e.g. a disk, by using a magnetic field for polarizing magnetic particles in
15 the recording layer. Information can be read from such a layer by optically detecting the Kerr rotation of polarized light, which is reflected from the relevant layer. For most magnetic media a relatively strong magnetic field is required to achieve a complete polarization of the magnetic material due to the high coercivity of the medium. Heating up a magnetic medium reduces drastically the threshold value of the magnetic field intensity that is necessary for a
20 complete polarization. Thermally assisted magnetic recording makes use of this phenomenon. In e.g. MO writing strategies with Laser Pulsed Magnetic Field Modulation (LP-MFM) a laser pulse is used to locally heat a magnetic medium while a magnetic field, which is synchronized with the timing of the laser pulse, polarizes the heated area. A magnetic head suitable for LP-MFM magneto-optical recording should have a magnetic-field-modulation
25 (MFM) coil and usually has a transparent guide for guiding a laser beam. The laser beam can be used both for heating a magnetic medium and for reading data from the magnetic medium via the detection of the Kerr effect. Usually, the transparent guide is arranged to be coaxial with the coil. In order to achieve sufficiently high magnetic field intensities with limited power consumption the inner radius of the coil is as small as possible.

WO 02/13188

PCT/EP01/08580

2

The size of the data bits which can be written by thermally assisted magnetic recording on a MO medium is limited by the size of the spot of the focussed laser beam and the thermal profile of the spot, and the thermal properties of the medium itself. The optical size of the spot depends on the wavelength (λ) of the laser light used and the numerical aperture (NA) of the optical path, yielding a diffraction limited spot with a radius (r) of the order of $0.61 \lambda/NA$. In near field recording a NA in excess of 1 is possible by using the evanescent waves, which occur at a surface of total internal reflection of a refractive optical component. A requirement is that the magnetic head, particularly the optical component thereof, is positioned with respect to the recording medium at a distance which is only a fraction of the wavelength of the laser light used. In order to realize higher recording densities in MO recording, such as near field recording, it is envisaged that the head to medium distance will be reduced towards the submicron range.

In a system for magnetic recording into a storage medium optical components are combined with a slider, the slider being carried by a suspension and being positioned below an objective lens of an actuator, an MFM coil being integrated in the slider. The slider is provided with an Air Bearing Surface (ABS) for flying on an air bearing at a surface of the storage medium during operation.

It is essential for such a slider that the coil of the magnetic head is a planar coil near to the plane of the ABS. In the method described in the previously mentioned IEEE paper this is realized by forming a ditch in a silicon wafer, whereafter a coil is buried in the ditch. A disadvantage of this known method is that making a ditch is laborious. Moreover, such a ditch is difficult to realize in most optical materials, such as multicomponent glasses, because these materials are in general difficult to etch. Since the coil structures are defined using photolithographic techniques, making a coil in a recess is a critical process because of the topography involved. In addition to this, an intermediate planarization between subsequent coil-layers is mechanically impossible.

It is an object of the invention to provide a simple method of manufacturing a magnetic head in which a planar coil is situated near to the head face.

This object is achieved by the method of manufacturing a magnetic head having a head face and including a magnetic coil which extends parallel to the head face, in which method the magnetic coil is formed at a first side of a first substrate, whereafter the first substrate provided with the magnetic coil is adhered, particularly glued, with its first side to a side of a second substrate, whereafter material of the first substrate is removed from a

WO 02/13188

PCT/EP01/08580

3

second side of the first substrate, which second side is turned away from the first side, to form the head face .

The method according to the invention involves only a few mask steps needed to realize a planar magnetic coil close to the head face. In the case of a magnetic head,
5 intended for use in a slider the magnetic head may be integrated in the slider, the head face forming at least a part of an air bearing surface.

In an embodiment of the method according to the invention the first substrate may be a substrate of silicon provided with a top layer, e.g. an oxide, such as SiO_2 or ZrO_4 or a hard material, such as diamond, this top layer being adjacent to the first side of the first
10 substrate. In general, the top layer forms the first side of the first substrate. The substrate of silicium may be a Si wafer. After adhering the first substrate to the second substrate at least a part of the silicon substrate is removed to form the head face. This can be effected by etching, preferably by means of a selective etching process which stops at the top layer, using e.g. hot KOH etchant, which is a selective etchant for Si and SiO_2 .

In an embodiment of the method according to the invention, after a step
15 involving the forming of a layer of a metal on the first substrate, at least one further step involving the forming of a layer of a non-conducting material and the forming of a further layer of a metal and the forming of interconnections between two neighboring layers of metal is performed to create the magnetic coil. The layers of metal can be formed by deposition,
20 e.g. by means of electro deposition, of a suitable metal, such as Cu. The layer of a non-conducting material can be formed by depositing e.g. an oxide, such as Al_2O_3 , or by spin coating of a polymer or in any other suitable way, such as spin-on-glass. The interconnection can be formed after holes have been formed in the layer of non-conducting material, e.g. by etching. The interconnection may also be formed by means of a lithographic process.

25 The non-conducting layer can be planarized by means of e.g. a polishing procedure, such as chemical-mechanical polishing, which improves the quality of the coil.

In an embodiment of the method according to the invention a substrate of a glass material is applied as the second substrate. This method results in a magnetic head having transparent portions. Such a head may be used as an MO-head and can have a light
30 guide.

In an additional step the transparent guide can be made out of a material having a refractive index matched with that of the glass substrate in order to avoid optical problems like unwanted reflections on interfaces.

WO 02/13188

PCT/EP01/08580

4

A further object of the invention is to provide a method of manufacturing a slider, in particular a slider applicable to a system for magneto-optical recording, the method enabling a magnetic coil, a defined air bearing surface and a defined location of the magnetic coil with respect to the air bearing surface to be realized in a limited number of method steps.

5 This further object is achieved by the method of manufacturing a slider having an air bearing surface and including a planar magnetic coil which extends parallel to the air bearing surface, in which method the magnetic coil is formed at a first side of a first substrate, whereafter the first substrate is adhered with its first side to a side of a second substrate, whereafter material of the first substrate is removed from a second side of the first
10 substrate, which second side is turned away from the first side, in order to form a face, whereafter the face is structured to form the air bearing surface. Standard technology can be used to carry out the few steps of the method according to the invention. Removal of material of the first substrate and structuring of the said face is effected preferably by etching. Virtually, the formed magnetic coil is part of a magnetic head integrated in the obtained
15 slider. Obviously, the magnetic coil has leads for electrical connections.

In an embodiment of the method of manufacturing a slider according to the invention on a silicon substrate a top layer of an insulating material is provided in order to form the first substrate, the top layer being adjacent to the first side, wherein a substrate of glass is applied as the second substrate, and wherein after adhering the first substrate to the
20 second substrate the silicon substrate is removed. In general, the top layer forms the first side. The substrate of silicon can be a wafer of silicon. The top layer can be an oxide, such as SiO_2 .

Since the top layer functions as a protective layer for the obtained slider, to preclude damage to the slider during use, e.g. owing to a crash with the surface of a recording medium or a bump into dust particles, a top layer of a hard material, such as a diamond-like
25 coating or a layer of ZrO_2 , is preferred. It is advantageous that the protective layer does not require any additional step, but is simply formed by the top layer of the first substrate.

An embodiment of the method of manufacturing a slider is characterized in that during forming of the magnetic coil a metallic layer is formed beside the magnetic coil, which metallic layer is at least partly removed to form a recess during structuring of the face
30 for forming the air bearing surface. The metallic layer is preferably formed by deposition of the same metallic material as used for forming the magnetic coil, e.g. Cu. Removal of metallic material can be effected simply by etching, e.g. by using a standard Cu etchant. The depth of the desired recess can be tuned by the thickness of the metallic layer.

WO 02/13188

PCT/EP01/08580

5

An embodiment of the method is characterized in that during forming of the magnetic coil a heat sink layer is formed beside the magnetic coil in the making. A suitable material for the heat sink layer is Cu, which can also be used as material for the magnetic coil. The heat sink layer is preferably positioned around or partly around the magnetic coil.

- 5 The heat sink layer in the resulting slider serves to transfer heat from the magnetic coil to one or more edges of the slider, where air cooling and radiation can be very effective in order to cool the slider. If desired, a real thermal connection can be provided between the heat sink and a cooling body with an enlarged area, or an active coolant, like a Peltier element.

- 10 In another embodiment a stack of interconnected coil layers is formed to create the magnetic coil.

It should be noticed that the claimed method of manufacturing a slider has advantages and effects similar to those obtained by the claimed method of manufacturing a magnetic head.

- 15 The invention further relates to a slider manufactured by means of the method according to the invention. The slider according to the invention has a planar magnetic coil adjacent to an air bearing surface and is preferably locally transparent, in such a manner that a light beam can axially pass through a central area of the coil. The slider has preferably the feature as defined in Claim 11.

- 20 Furthermore, the invention relates to a system for magnetically or magneto-optically recording information into a storage medium, the system including the slider according to the invention.

With reference to the Claims, it is to be noted that various characteristic features as defined in the set of Claims may occur in combination.

- 25 The above-mentioned and other aspects of the invention are apparent from and will be elucidated, by way of non-limitative example, with reference to the embodiments described hereinafter.

In the drawings:

- Figures 1 to 8 represent diagrammatically various steps of an embodiment of a method according to the invention, in which

- 30 Figure 8 also shows a first embodiment of the slider according to the invention,

Figure 9A shows diagrammatically in a cross section al view a second embodiment of the slider according to an invention,

WO 02/13188

PCT/EP01/08580

6

Figure 9B shows the second embodiment in a section al view taken on the line IXB-IXB in Figure 9A, and

Figure 10 shows diagrammatically in a perspective view an embodiment of a system according to the invention.

5 An embodiment of the method according to the invention of manufacturing a slider 10 will now be described with reference to Figures 1 to 8. This embodiment starts from a substrate 1 of silicon which substrate 1 may form part of a Si-wafer. An insulation material, particularly an oxide such as SiO_2 or Al_2O_3 , is deposited on a main face of the substrate 1, for example, by thermal oxidation, by means of sputtering or by vapor deposition, to form a thin
10 top layer 3 having a thickness of e.g. $0.5\ \mu\text{m}$. The substrate 1 and the top layer 3 together form a first substrate having a first side 5a and a second side 5b parallel to the first side 5a. A first conductive or metallic layer 7a provided with one or more coil turn sections is formed at the first side 5a of the first substrate, for example, by means of sputter deposition or electro deposition of copper or another suitable electrically conductive material. Then a non-
15 conducting layer 7b is formed on the first conductive layer 7a by e.g. deposition of SiO_2 or Al_2O_3 , or by spin-coating of a polymer. Thereafter, a second conductive layer 7c is formed on the insulating layer 7b and an interconnection between the first and second conductive layers is made, e.g. by locally etching the non-conducting layer 7b before the second conductive layer 7c is formed.

20 The layers 7a, 7b and 7c together form a planar magnetic coil 7 having a coil axis 7A. It is to be noted that in another embodiment the coil 7 may have only one conductive layer. After forming the coil 7 the first substrate is adhered, particularly glued, with its first side 5a, which side has been shifted in this embodiment owing to technology steps, to a side 9a of a second substrate 9 of e.g. glass. The second substrate 9 may form part of a glass
25 wafer. A suitable glue is e.g. acrylate resin varnish; 1,6-hexanedioldiacrylate. In a following step the substrate 1 is removed, particularly etched away, in e.g. hot KOH, resulting in a face 13. Subsequently, the face 13 is structured by first locally removing the top layer 13, e.g. by locally etching away insulation material, and then locally removing material of one or more laid open portions 7B of the first conductive layer 7a, e.g. by locally etching, in order to
30 create an air bearing surface 15, which is the face 13 provided with one or more recessed portions 13a. In the case that Cu is used as the conductive material for the coil 7 a standard Cu etchant may be used to form the air bearing surface 15. The depth of the recessed portion or portions 13a can be tuned by using multiple metallic layers.

WO 02/13188

PCT/EP01/08580

7

During use of the slider the air bearing surface 15 of the slider obtained by the above described method serves to control the flow of air produced between a surface of a moving storage medium and the slider 10 located adjacent said surface, in order to avoid contact of the slider with the storage medium.

5 It is to be noticed that the above-described method can also be used for manufacturing a magnetic head. In that case the method steps as shown in the Figures 7 and 8 can be omitted. This means that the product shown in Figure 6 may be a magnetic head, the face 13 forming a head face. Both in the case of the slider and in the case of the magnetic head the top layer may function as a protective layer.

10 It is to be noted further that the slider as shown in Figure 8 has a transparent coil center 7C and is transparent along the coil axis 7A by a suitable choice of transparent materials, as a result of which the slider is transparent to a beam of light going through said center.

In a variant of the above-described embodiment a heat sink layer is formed
15 during forming of the coil 7. Figures 9A and 9B show an embodiment of the slider according to the invention provided with a heat sink 17. Elements of this variant which correspond to similar elements of the embodiment already described have the same reference signs. In the relevant variant the heat sink is formed simultaneously with the coil 7 by means of deposition of the same metal as deposited for forming the magnetic coil 7 and its connection faces 7f₁,
20 and 7f₂. The heat sink 17 is positioned adjacent to, i.e. at least partly around and/or above or beneath, the magnetic coil 7, and serves to transfer heat from the turn or turns of the coil to the borders of the slider, where convection and radiation effectively cool the slider during its use. In a special embodiment a thermal connection may be provided between the heat sink and a cooling body with an enlarged area, or an active coolant, like a Peltier element.

25 An embodiment of the system according to the invention, shown in Figure 10, is suitable for writing and/or reading a magneto-optical information disk 100. The disk 100 is rotably supported by an electrically drivable spindle mounted in a base. During use the disk 100 is rotated in a direction of rotation, indicated by the arrow A. The system includes an arm 102 translatably held on the base and having a flexural member 102a carrying an
30 embodiment of the slider according to the invention, here indicated by the numeral 110, having a transparent body indicated by the numeral 104. An electrical drive is provided to translate the arm 102, the slider 110 being moved in radial directions, indicated by the arrow B, during translation over the disk 100. During writing and/or reading the air-bearing surface of the slider is located opposite to and at a distance from a main face of the disk 100. The arm

WO 02/13188

PCT/EP01/08580

8

102 carries a lens section 106 having an optical axis 106a going through the transparent center of the magnetic coil of the slider 110. Here, the coil is indicated by the numeral 107.

The system according to the invention can be a data storage system.

Alternatively, the system may be an audio and/or video system. A rotatable arm may be used
5 instead of a translatable arm.

WO 02/13188

PCT/EP01/08580

9

CLAIMS:

1. A method of manufacturing a magnetic head having a head face and including a magnetic coil which extends parallel to the head face, in which method the magnetic coil is formed at a first side of a first substrate, whereafter the first substrate provided with the magnetic coil is adhered with its first side to a side of a second substrate, whereafter material
5 of the first substrate is removed from a second side of the first substrate, which second side is turned away from the first side, to form the head face.
2. A method as claimed in Claim 1, wherein a substrate of silicon provided with a top layer of an insulating material is used as the first substrate, the top layer being adjacent
10 to the first side.
3. A method as claimed in Claim 2, wherein after a step involving the forming of a layer of a metal on the first substrate, at least one further step involving the forming of a layer of a non-conducting material and the forming of a further layer of a metal and the
15 forming of interconnections between two neighboring layers of metal is performed to create the magnetic coil.
4. A method as claimed in Claim 1, wherein a substrate of a glass material is used as the second substrate.
20
5. A method of manufacturing a slider having an air bearing surface and including a planar magnetic coil which extends parallel to the air bearing surface, in which method the magnetic coil is formed at a first side of a first substrate, whereafter the first substrate is adhered with its first side to a side of a second substrate, whereafter material of
25 the first substrate is removed from a second side of the first substrate, which second side is turned away from the first side, in order to form a face, whereafter this face is structured to form the air bearing surface.

WO 02/13188

PCT/EP01/08580

10

6. A method as claimed in Claim 5, wherein on a silicon substrate a top layer of an insulation material is provided in order to form the first substrate, the top layer being adjacent to the first side, wherein a substrate of glass is used as the second substrate, and wherein the silicon substrate is removed after adhering of the first substrate to the second substrate.

10

7. A method as claimed in Claim 5, wherein during forming of the magnetic coil a metallic layer is formed beside the magnetic coil, which metallic layer is at least partly removed to form a recess during structuring of the face to form the air bearing surface.

15

8. A method as claimed in Claim 5, wherein during forming of the magnetic coil a heat sink layer is formed beside the magnetic coil in the making.

9. A method as claimed in Claim 5, wherein a stack of interconnected coil layers is formed to create the magnetic coil.

10. A slider manufactured by the method as claimed in the Claims 5 to 9.

11. A slider as claimed in Claim 10, wherein the top layer forms a protective layer for the slider.

12. A system for magnetically or magneto-optically recording information into a storage medium, the system including the slider as claimed in Claim 10.

WO 02/13188

PCT/EP01/08580

1/5




FIG. 1




FIG. 2




FIG. 3




FIG. 4

WO 02/13188

PCT/EP01/08580

2/5




FIG. 5




FIG. 6

WO 02/13188

PCT/EP01/08580

3/5




FIG. 7




FIG. 8

WO 02/13188

PCT/EP01/08580

4/5




FIG. 9A




FIG. 9B

WO 02/13188

PCT/EP01/08580

5/5




FIG. 10

INTERNATIONAL SEARCH REPORT

Int ional Application No
PCT/EP 01/08580

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 G11B5/17 G11B11/105 G11B5/60		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 G11B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the International search (name of data base and, where practical, search terms used) EPO-Internal, PAJ		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 642 336 A (ALBERTINI JEAN BAPTISTE ET AL) 24 June 1997 (1997-06-24) the whole document ---	1,5,10, 12
A	PATENT ABSTRACTS OF JAPAN vol. 008, no. 010 (P-248), 18 January 1984 (1984-01-18) -& JP 58 169330 A (FUJITSU KK), 5 October 1983 (1983-10-05) abstract figures ---	1,5,10, 12
A	EP 0 994 466 A (SHARP KK) 19 April 2000 (2000-04-19) column 13, line 3 - line 25; figures 13,14 --- -/--	1
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : *A* document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the International filing date *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) *O* document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the International filing date but later than the priority date claimed *T* later document published after the International filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. *&* document member of the same patent family		
Date of the actual completion of the International search 20 December 2001		Date of mailing of the International search report 03/01/2002
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3018		Authorized officer Fux, J

INTERNATIONAL SEARCH REPORT

International Application No
PCT/EP 01/08580

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	PATENT ABSTRACTS OF JAPAN vol. 1998, no. 03, 27 February 1998 (1998-02-27) & JP 09 305903 A (SONY CORP), 28 November 1997 (1997-11-28) abstract ---	
A	PATENT ABSTRACTS OF JAPAN vol. 1999, no. 09, 30 July 1999 (1999-07-30) & JP 11 120642 A (SONY CORP), 30 April 1999 (1999-04-30) abstract ---	
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 06, 22 September 2000 (2000-09-22) & JP 2000 090403 A (CANON INC), 31 March 2000 (2000-03-31) abstract ---	
A	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 02, 29 February 2000 (2000-02-29) & JP 11 316901 A (CANON INC; ASAHI CHEM IND CO LTD), 16 November 1999 (1999-11-16) abstract -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

Int'l. Application No

PCT/EP 01/08580

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5642336	A	24-06-1997	FR 2705488 A1 EP 0624871 A2 JP 6349004 A US 5544131 A	25-11-1994 17-11-1994 22-12-1994 06-08-1996
JP 58169330	A	05-10-1983	NONE	
EP 0994466	A	19-04-2000	JP 2000123303 A EP 0994466 A2	28-04-2000 19-04-2000
JP 09305903	A	28-11-1997	NONE	
JP 11120642	A	30-04-1999	EP 0910078 A2	21-04-1999
JP 2000090403	A	31-03-2000	NONE	
JP 11316901 3	A		NONE	